

# Well Casing Pipe



ASTM D2241  
ASTM D1784 Cell Class 12454

Joint ASTM D3139

1700 S. Lincoln St. Siloam Springs, AR. 72761

## Markets



Irrigation



Potable

## Description

### Available Pipe Sizes

<b>SDR 17</b>	4/1/2", 5", 6"	<b>SDR 21</b>	6-1/8"
<b>Sch. 40</b>	4", 4/1/2", 5", 6", 8", 10", 12", 16"		
<b>SDR 21</b>	4", 5", 6", 8", 10", 12"	<b>SDR 27.6</b>	6-1/4"
<b>SDR 26</b>	4", 4/1/2", 5", 6", 8", 10", 12", 16"		

Nominal Laying Length = 20 feet (Laying length are 20' plus the BE in accordance with AWWA and CSA Standards)

## Slotting Sizes and Dimensions

SDR 26 Class 160# Slotted Belled End				
Size	Slot Width	Slot Space	Row #	Open Area
4"	0.035	0.25	4	214
4-1/2"	0.035	0.25	4	243
5"	0.020	0.25	4	139
	0.035	0.25	4	279
6"	0.035	0.25	5	308
8"	0.035	0.25	6	407
	0.050	0.25	6	561
	0.085	0.25	6	849
10"	0.035	0.25	7	517
	0.050	0.25	7	712
	0.085	0.25	7	1077
12"	0.035	0.25	8	547
	0.050	0.25	8	754
	0.085	0.25	8	1139
16"	0.035	0.25	10	626
	0.050	0.25	10	863
	0.085	0.25	10	1304

Schedule 40 Slotted Belled End				
Size	Slot Width	Slot Space	Row #	Open Area
4"	0.020	0.25	4	116
	0.035	0.25	4	194
4-1/2"	0.020	0.25	4	129
	0.035	0.25	4	227
5"	0.035	0.25	5	265
6"	0.035	0.25	5	299
8"	0.050	0.25	6	561
	0.085	0.25	6	849
10"	0.035	0.25	7	480
	0.050	0.25	7	687
	0.085	0.25	7	1038
12"	0.035	0.25	8	531
	0.050	0.25	8	759
	0.085	0.25	8	1148
16"	0.035	0.25	10	723
	0.050	0.25	10	996
	0.085	0.25	10	1505

SDR 21 Class 200# Slotted Belled End				
Size	Slot Width	Slot Space	Row #	Open Area
4"	0.035	0.25	4	201
5"	0.020	0.25	4	130
	0.035	0.25	4	265
6"	0.035	0.25	5	285
8"	0.035	0.25	6	372
	0.050	0.25	6	513
	0.085	0.25	6	775
10"	0.035	0.25	7	467
	0.050	0.25	7	655
	0.085	0.25	7	972
12"	0.035	0.25	8	469
	0.050	0.25	8	646
	0.085	0.25	8	977



SDR 17 Slotted Belled End				
Size	Slot Width	Slot Space	Row #	Open Area
4-1/2"	0.020	0.25	4	123
5"	0.020	0.25	4	120
6"	0.020	0.25	5	143
	0.035	0.25	5	255

Customer Service 1-800-643-3470

This Information may have updates. Please visit: [jetstreampipes.com](http://jetstreampipes.com) for all updated information.

**THIS PRODUCT IS MADE IN AMERICA**

Printed 2021

# Well Casing Pipe

## SDR26 Class 160 WC

Size	Average OD	Nominal ID	Min Wall	Bell Depth	Bell OD	Insertion depth	Weigh per foot	Pallet footage	order units	FT Truck
4"	4.500	4.134	0.173	5.750	4.895	1/2-2/3 interference dry fit	1.562	720	2	17,280
4-1/2"	4.950	4.547	0.190	6.000	5.385	1/2-2/3 interference dry fit	1.892	480	2	11,520
5"	5.563	5.108	0.214	6.500	6.055	1/2-2/3 interference dry fit	2.399	420	2	10,080
6"	6.625	6.084	0.255	7.000	7.208	1/2-2/3 interference dry fit	3.409	600	4	7,200
8"	8.625	7.921	0.332	7.500	9.384	1/2-2/3 interference dry fit	5.793	360	4	4,320
10"	10.750	9.874	0.413	7.750	11.691	1/2-2/3 interference dry fit	8.993	220	4	2,640
12"	12.750	11.711	0.490	8.250	13.863	1/2-2/3 interference dry fit	12.701	80	2	2,240
16"	16.000	14.694	0.616	8.250	17.400	1/2-2/3 interference dry fit	19.996	120	4	1,440

## SDR21 Class 200 WC

Size	Average OD	Nominal ID	Min Wall	Bell Depth	Bell OD	Insertion depth	Weigh per foot	Pallet footage	order units	FT Truck
4"	4.500	4.046	0.214	5.750	4.989	1/2-2/3 interference dry fit	1.907	720	2	17,280
5"	5.563	5.001	0.265	6.500	6.167	1/2-2/3 interference dry fit	2.945	420	2	10,080
6"	6.625	5.955	0.316	7.000	7.344	1/2-2/3 interference dry fit	4.181	600	4	7,200
6-1/8"	6.900	6.212	0.329	0.7.250	8.590	1/2-2/3 interference dry fit	4.518	360	2.4	7,200
8"	8.625	7.756	0.410	7.500	9.558	1/2-2/3 interference dry fit	7.082	360	4	4,320
10"	10.750	9.667	0.511	7.750	11.909	1/2-2/3 interference dry fit	11.001	220	4	2,640
12"	12.750	11.465	0.606	8.250	14.123	1/2-2/3 interference dry fit	15.449	80	2	2,240

## Sch40 WC

Size	Average OD	Nominal ID	Min Wall	Bell Depth	Bell OD	Insertion depth	Weigh per foot	Pallet footage	order units	FT Truck
2"	2.375	2.047	0.154	4.500	2.729	1/2-2/3 interference dry fit	0.712	2,800	2	67,200
4"	4.500	3.998	0.237	5.750	5.039	1/2-2/3 interference dry fit	2.111	720	2	17,280
4-1/2"	4.950	4.426	0.248	6.000	5.511	1/2-2/3 interference dry fit	2.441	480	2	11,520
5"	5.563	5.001	0.265	6.500	6.167	1/2-2/3 interference dry fit	2.945	420	2	10,080
6"	6.625	6.031	0.280	7.000	7.264	1/2-2/3 interference dry fit	3.728	600	4	7,200
8"	8.625	7.921	0.332	7.500	9.384	1/2-2/3 interference dry fit	5.724	360	4	4,320
10"	10.750	9.976	0.365	7.750	11.583	1/2-2/3 interference dry fit	7.700	220	4	2,640
12"	12.750	11.889	0.406	8.250	13.675	1/2-2/3 interference dry fit	10.183	80	2	2,240
16"	16.000	14.940	0.500	8.250	17.140	1/2-2/3 interference dry fit	16.404	120	4	1,440

## SDR17 WC

Size	Average OD	Nominal ID	Min Wall	Bell Depth	Bell OD	Insertion depth	Weigh per foot	Pallet footage	order units	FT Truck
4-1/2"	4.500	4.338	0.291	6.000	5.601	1/2-2/3 interference dry fit	2.831	480	2	11,520
5"	5.563	4.870	0.327	6.500	6.305	1/2-2/3 interference dry fit	3.581	420	2	10,080
6"	6.625	5.798	0.390	7.000	7.510	1/2-2/3 interference dry fit	5.102	600	4	7,200

## SDR27.6 WC

Size	Average OD	Nominal ID	Min Wall	Bell Depth	Bell OD	Insertion depth	Weigh per foot	Pallet footage	order units	FT Truck
6-1/4"							3.478	360	2.4	7,200

